

U.S. Serial No. 10/644,564  
Amendment Dated August 23, 2005  
Response To Office Action Dated March 21, 2005

---

### Amendments to the Specification

Please replace the paragraph beginning at page 4, line 13 with the following paragraph:

In at least one embodiment, as shown in Figures 2 and 3, the fuel system 10 may be composed of a first premix injector assembly 14 and a second premix injector assembly 16, both of which may be formed from one or more injectors 12. The first premix injector assembly 14 may be formed from two or more injectors 12 positioned adjacent to each other in a combustor 18 of a turbine engine 20. The injectors 12 of the first premix injector assembly 14 may be referred to as "A" injectors. In at least one embodiment, the first premix injector assembly 14 may be formed from four or more injectors. Likewise, the second premix injector assembly 16 may be formed from two or more injectors 13 positioned adjacent to each other in a combustor 18 of a turbine engine 20. The injectors 13 of the second premix injector assembly 16 may be referred to as "B" injectors. In at least one embodiment, the second premix injector assembly 16 may be formed from four or more injectors 13. The first and second premix injector assemblies 14 and 16 may be aligned so that the injectors 12 and 13 emit fuel generally parallel to a longitudinal axis of the combustor 18. Additional C-Stage fuel injectors 49 are present.

{WP253793;1}